


SWITCHING POWER SUPPLIES

IZM 123 SERIES

Module-type power supply

- **Wide range of input voltages AC or DC:**
87V÷260V AC, 90V÷350V DC
- **Power output: 12W**
- **3 output voltages**
- **3-year guarantee**
- **Control and security systems**
- **High efficiency**
- **Full voltaic separation**



IZM 123 is a series of switching power supplies with the maximum power output of 12W and general-purpose supply voltage range: 87V - 260V AC or 90V - 350V DC. The power supplies are made in module form, in ABS casings to be mounted on a printed board. It is designed for application in measuring apparatus, industrial instrumentation and control equipment, telecommunications and also in microprocessor-based systems.

TECHNICAL DATA

Input

Input voltage	87V to 260V AC 90V to 350V DC
Input frequency range	40Hz to 440Hz
Interference emission level	to EN 55022

Output


Stabilisation of U_{input} variations	$\leq 0.3\%$
Stabilisation of I_{load} variations	$\leq 0.3\%$
Temperature coefficient	0.04%/°C
Power output at 50°C	12W
Max. Iout for U2, U3	250 mA
Pulsating voltage	$U_t \leq 100mV_{pp}$ $U_{trms} \leq 10mV$

General

Modulation frequency	$f_p \leq 100kHz$
Modulation mode:	PWM - Flyback
Hold time 50%/Un/Pmax	$t_p \geq 30ms$
Efficiency (dependant on U_{output})	70÷80%
Dimensions	75 x 50 x 25
Insulation strength	input-output 8mm input-ground 4mm
Operating temperature	-10°C to +55°C
ABS casing covered with a chemo-hardening compound	

The construction satisfies the safety and electromagnetic compatibility requirements of the relevant EC standards.

MODEL	OUTPUTS		
	Output 1 V_{nom}/I_{max}	Output 2 V_{nom}/I_{max}	Output 3 V_{nom}/I_{max}
IZM-123-51212	5V/1.2A	12V/0.25A	12V/0.25A
IZM-123-51515	5V/1.2A	15V/0.2A	15V/0.2A
IZM-123-52424	5V/1.2A	24V/0.1A	24V/0.1A



ELPLAST® Sp. z o.o.

58-100 ŚWIDNICA, ul. Armii Krajowej 9, www.elplast.pl, info@elplast.pl